

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **770-LINE WEATHERMAX HBR PART A**

Recommended use of the chemical and restrictions on use: Part A of a two pack polyurethane coating applied by brush, roller or spray. Also refer to the MSDS for Part B.

Supplier: Dulux New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd
ABN 55 133 404 118
Co. 2355191

Street Address: 150 Hutt Park Road
Lower Hutt,
New Zealand

Telephone Number: +64 4 576 6400
Facsimile: +64 4 576 6496
Emergency Telephone: **0 800 734 607 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: WARNING

Subclasses:

Subclass 3.1 Category C (medium hazard) - Flammable Liquids.

Subclass 6.3 Category B - Substances that are mildly irritating to the skin.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 9.1 Category C - Substances that are harmful in the aquatic environment.

Surface Coatings and Colourants (Flammable) Group Standard 2006



Hazard Statement(s):

H226 Flammable liquid and vapour.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

Safety Data Sheet



Precautionary Statement(s):

Prevention:

P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P273 Avoid release to the environment.

Response:

P370+P378 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet for extinction.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).
P363 Wash contaminated clothing before re-use.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS Number | Proportion | Hazard Codes |
|--|------------|------------|----------------|
| Ethyl 3-ethoxy propionate | 763-69-9 | 10-<30% | H226 |
| Propylene glycol monomethyl ether acetate | 108-65-6 | 10-<30% | H226 |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | 1-<10% | H350 H340 H304 |
| Ingredients determined not to be hazardous | - | to 100% | - |

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. A component of this material can be absorbed through the skin with resultant toxic effects. Seek immediate medical assistance.

Safety Data Sheet

**Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

Hazchem or Emergency Action Code: · 3Y**Specific hazards arising from the substance or mixture:**

Flammable liquid. On burning will emit toxic fumes, including those of oxides of carbon .

Special protective equipment and precautions for fire-fighters:

Keep containers cool with water spray. If safe to do so, remove containers from path of fire. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to source of ignition and flash back.

Conditions for safe storage, including any incompatibilities: Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Department of Labour (Health & Safety).

Safety Data Sheet



Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: I - OVERALLS, SAFETY SHOES, FACE SHIELD OR AIR MASK, GLOVES (Long).



FOR SPRAY APPLICATION: Wear overalls, impervious gloves and a positive pressure air supplied full-face respirator. Apply in a spray booth fitted with an effective exhaust system and comply with local regulations applicable to spray painting. The spray booth should be isolated from other people whilst spraying is in progress and until all spray mist has been effectively dispersed. Catalysed product deteriorates on contact with moisture liberating gas. The can may be under pressure. Before opening, place cloth over lid to prevent contents splashing. To open, hold hand firmly on cloth over lid to prevent lid flying off, then lever lid off gradually. Avoid breathing dust when sanding. Wet sand or use a dust mask. Always wash hands before smoking, eating, drinking or using the toilet.

FOR BRUSH AND ROLLER APPLICATION: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------------------|--|
| Physical state: | Viscous liquid |
| Colour: | Coloured |
| Odour: | Solvent |
| Solubility: | Soluble in organic solvents. Insoluble in water. |
| Specific Gravity: | 1-1.5 @ 20°C |
| Relative Vapour Density (air=1): | >1 |
| Vapour Pressure (20 °C): | Not available |
| Flash Point (°C): | 42 |
| Flammability Limits (%): | Not available |
| Autoignition Temperature (°C): | Not available |
| % Volatile by Volume: | Not available |
| Solubility in water (g/L): | Negligible |
| Melting Point/Range (°C): | Not applicable |
| Boiling Point/Range (°C): | Not available |
| Decomposition Point (°C): | Not available |
| pH: | Not applicable |
| Viscosity: | Not available |
| Evaporation Rate: | Not available |

10. STABILITY AND REACTIVITY

Reactivity: No information available.

Product Name: 770-LINE WEATHERMAX HBR PART A
Substance No: 000000002265

Issued: 10/07/2013
Version: 5

Safety Data Sheet



| | |
|--|---|
| Chemical stability: | Stable under normal conditions of use. |
| Possibility of hazardous reactions: | Hazardous polymerisation will not occur. |
| Conditions to avoid: | Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame. |
| Incompatible materials: | Incompatible with oxidising agents. |
| Hazardous decomposition products: | Oxides of carbon. |

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

| | |
|----------------------|--|
| Ingestion: | Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. Breathing in vomit may lead to aspiration pneumonia (inflammation of the lung). |
| Eye contact: | May be an eye irritant. |
| Skin contact: | Contact with skin will result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. Component/s of this material can be absorbed through the skin with resultant toxic effects. |
| Inhalation: | Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. |

Acute toxicity: No LD50 data available for the product. For the constituent Ethyl 3-ethoxy propionate (1):

Oral LD50 (rat): >5000 mg/kg

Dermal LD50 (rabbit): 4080 mg/kg

Inhalation LC50 (rat): >998 ppm/6 Hrs

Chronic effects: No information available for the product. For the intermixed paint (mix of Parts A&B): May cause skin sensitisation. Inhalation of aerosol droplets may cause respiratory sensitisation in some susceptible workers with asthma-like symptoms. Repeated exposure may lead to permanent respiratory disability (2).

12. ECOLOGICAL INFORMATION

| | |
|--------------------|--------------------------------|
| Ecotoxicity | Avoid contaminating waterways. |
|--------------------|--------------------------------|

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Refer to local government authority for disposal recommendations. Dispose of material through a licensed waste contractor.

Safety Data Sheet



14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



UN No: 1263
Transport Hazard Class: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name or Technical Name: PAINT
Hazchem or Emergency Action Code: - 3Y

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1263
Transport Hazard Class: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name or Technical Name: PAINT

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1263
Transport Hazard Class: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name or Technical Name: PAINT

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses:

Subclass 3.1 Category C (medium hazard) - Flammable Liquids.
Subclass 6.3 Category B - Substances that are mildly irritating to the skin.
Subclass 6.5 Category B - Substances that are contact sensitisers.
Subclass 9.1 Category C - Substances that are harmful in the aquatic environment.

Surface Coatings and Colourants (Flammable) Group Standard 2006

Safety Data Sheet

**Hazard Statement(s):**

H226 Flammable liquid and vapour.
H316 Causes mild skin irritation.
H317 May cause an allergic skin reaction.
H402 Harmful to aquatic life.

16. OTHER INFORMATION

- (1) Supplier Safety Data Sheet; 12/ 2012.
(2) In 'Exposure Standards for Atmospheric Contaminants in the Occupational Environment 3rd Edition (Ed. NOHSC), Australian Government Publishing Service Canberra (1995).

Reason(s) for Issue:

Revised Primary SDS
Change in Personal Protection Requirements

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

DuluxGroup owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.